

HAWKEYE PRODUCT LINE CARD



REDTAIL HAWK DRY SEAL GAUGE HEAD

This sealed float-activated level gauge features a unique dry-seal design making it superior to other sealed level gauging systems. It can be relied upon to measure storage and production tanks, with an 20+ year history and over 8000 units installed globally.



SPARROWHAWK OPEN GAUGE HEAD

When emission prevention and control are not required, the Sparrowhawk Model is the reliable, economical choice. The compact and easy-to-install level gauge works on any size storage, production or mud tank.



GOSHAWK LEVEL TRANSMITTER

The Goshawk transmitter adds 4-20 mA electronic level indication to the Redtail Hawk and Roadside Hawk Sealed Gauge Head Systems..



POLYETHYLENE & STAINLESS FLOATS

Hawkeye's Horizontal Polyethylene floats are the industry standard for level gauging systems. Accept no imitations. 316L Stainless Floats are also available for high temperature service.



COOPER'S HAWK TANK LEVEL GAUGE

The Cooper's Hawk Tank Level Gauge offers an easy to read visual level measurement for bulk product tanks, thanks to the high-visibility sight glass. The Cooper's Hawk also includes a rate scale for metering chemical injection pumps.




GREYHAWK HORIZONTAL LEVEL GAUGE

The Greyhawk Level Indication system provides an effective and economical way to directly gauge level in knock-out or other horizontal tanks.



SERIES 4000 MARSH HAWK

The Marsh Hawk is a deep-set pressure and vacuum relief venting gauge hatch for atmospheric tanks. With recessed seals for both pressure and vacuum relief, the Marsh Hawk resists freezing, providing reliable year-round operation.



SERIES 6000 PVRV

A dedicated relief vent featuring Hawkeye's patent-pending UBR valve technology. The Series 6000 PVRV is available in pressure + vacuum relief, as well as pressure-only and vacuum only configurations, as well as end-of-line and in-line styles.




ROADSIDE HAWK DRY SEAL GAUGE HEAD

Using the same principles as the Redtail Model, the Roadside is a compact design suited for higher pressure applications as well as underground tanks. The renowned Hawkeye durability and maintenance-free design are evident in this level gauge.




MODEL 750 GAUGE HEAD SYSTEM

The Model 750 Gauge Head provides a simple and economical gauging choice. The easy-to-install gauge works on any size storage, production or mud tank. Also available with a Liquid Seal (LS) option, for low cost vapor control.




LEVEL SWITCHES

Hawkeye Industries Inc. offers electric and pneumatic gaugeboard based single-point level indication products ideal for level alarms, emergency shut downs, pump start /stop and any other application that requires activation based on tank fluid level.




GAUGING SYSTEM COMPONENTS

Complete your tank level indication system, with float guides, anchors, indicators and gauge boards with volume / height decals made to your specification.



COOPER'S HAWK BARREL LEVEL GAUGE

The Cooper's Hawk Tank Barrel Gauge is an application-specific level gauge featuring easy to read visual level measurement for standard sized 55 gallon barrels. The Cooper's Hawk also includes a rate scale for metering chemical injection pumps.



SERIES 1200 SKIMMERS

The Series 1200 Floating Skimmer provides an effective non-metallic solution to skimming product from the surface of tank contents, regardless of the overall tank level.



SERIES 5000 EPRV

The Hawkeye Series 5000 Emergency Pressure Relief Vent (EPRV) is a weighted manway cover for liquid storage and process tanks. The EPRV opens in the event of an abnormal pressure rise to relieve overpressures beyond normal venting capacity of standard vents.



MODEL 200 & 300 TVTH

An economical and traditional venting gauge hatch suitable for sweet (Model 200) and sour (Model 300) service.

LEVEL INDICATION


TANKAGE LINES

VAPOUR CONTROL




HAWKEYE PRODUCT LINE CARD

POLYETHYLENE & PIPELINE



ID CONTROLLED HDPE-STEEL TRANSITION FITTINGS

Polyethylene to steel weld-end non-ID obstructed fittings seamlessly connect polyethylene pipe to steel pipe. Hawkeye Industries Inc.'s ID Controlled Transition Fitting are PE 100 standard, and offer a piggable alternative to traditional, non-ID controlled fittings.



TRACER WIRE

Tracer, or locating wire, buried next to non-metallic pipe and conduit (i.e. thermoplastic gas pipelines), allows line detection with conventional equipment.



INNERLYNX END SEALS

Hawkeye Industries Inc. offers INNERLYNX End Seals, used to form a mechanical seal between carrier pipes and casings, openings in vaults, tanks and walls.



FABRICATED & MOLDED HDPE FITTINGS

Polyethylene fittings, manufactured from raw billet materials, or injection molded come in a wide range of styles and sizes suitable for new or existing gas pipeline systems.



RACI CASING SPACERS

Innovative RACI spacers isolate carrier pipes from casing pipe in a simple and cost-effective manner. The unique RACI design provides projections around the entire circumference of the carrier pipe, and has no fasteners to scratch or mar the casing during installation.



WRAP AROUND END SEALS

Flexible, durable and economical end seal solution.

PRODUCTION & DOWNHOLE



TUBING DRAIN

This Tubing drain significantly out-performs drains available today. The pressure activated device, allows oil and other sediments to flow from the tubing string, enabling safer, cleaner, and easier well maintenance.



DYNAMIC TORQUE ANCHOR

The Dynamic Torque Anchor is a multi-lobe active-anchor no-turn tool designed to resist clockwise rotation of the tubing string by anchoring it to the casing.



TUBING CENTRALIZER

Flexible, durable and economical way to protect and insulate the tubing string



POLISHED ROD BULLETS

The Hawkeye Industries Inc. Polished Rod Bullets come in an array of rod and box sizes, offering a wide range of thread and packing protection.



CRITICAL FLOW PROVER

The critical flow prover (CFP), uses principles of compressible flow to determine flow rate by measuring only upstream pressure and temperature. The rugged design of this critical flow prover ensures accurate, repeatable results.




TUBING SHEAR

The Tubing Shear is a box-by-pin tubing coupling used when release of the tubing string in tension is desired. The robust interlocking castellation design resists torque, and internal supports resist compression.



PUMP OUT PLUGS

The Hawkeye Industries Inc. pump-out plug is a premium, cost-effective temporary tubing plug. The single use pressure activated device, located at the bottom end of the tubing string, temporarily seals the string ID for testing, setting packers and keeping debris out.



CONELOK™ SHEAR COUPLINGS

Hawkeye Industries Shear Couplings for Sucker Rods provide consistent tensile shear loads, while not compromising the torsional strength of the sucker rod string.



SEATING CUPS

The proprietary material used on Hawkeye's Seating cups allows high temperature operation.



2110 70 Ave NW
Edmonton, AB, Canada T6P 1N6
Toll Free: (800) 910-4295
Phone: (780) 490-4295
Fax: (780) 490-4290
www.hawk-eye.com

HAWKEYE PRODUCTS ARE AVAILABLE IN YOUR AREA FROM: